



877-351-9573

DM-930 Automotive Digital Multimeter

Comparison with Fluke 88V/A Basic Kit

Tools and Equipment for professional technicians and educators

Feature	PDI DM-930	Fluke 88V
UL Certification	Yes	Yes
CAT IV 600V	Yes	Yes
CAT III 1000V	Yes	Yes
Fused Protection	Yes	Yes
Max Amp	20A	10A
Low Amp	400mA	440mA
Battery	9V	9V
Basic DC Accuracy	0.50%	0.10%
True RMS	No	Yes
Bar graph	Yes	Yes
Digits	4 1/2	3 3/4
Display Counts	4000	20000
Resistance	40MΩ	50MΩ
AC/DC Volts	600V	1000V
Capacitance	40mF	10mF
AC/DC Current	Yes	Yes
Micro Amps	Yes	No
Frequency	400kHz	200kHz
Temperature	+1000°C	+1090°C
Continuity	Yes	Yes
Max/Min	Yes	Yes
Diode Test	Yes	Yes
Data hold	Yes	Yes
Peak	Yes	Yes
Backlight	Yes	Yes
ms-Pulse	Yes	Yes
Dwell Angle	Yes	?
RPM	Yes	No
Auto Power Off	Yes	Yes
Low Battery Indicator	Yes	Yes
Protective Case	Co-Molded Rubber Body	Removable Boot
Waterproof	Yes (IP67)	No (IP30)
Dust proof	Yes (IP67)	No (IP30)
Tilt Stand	Yes	Yes
Standard Accessories	Test Leads, Alligator Clips, Inductive Pickup (RPM), Bead Style Thermocouple, TC Adapter, Magnetic Hanging Strap, Battery, Tool Bag	Test Leads, Boot, Battery

[More details on the DM-930 meter available at AESwave.com](#)

Catch a Wave!